

D Static powered lift tables

- 100% welded bottom frame and integrated hydraulics.
- Includes a simple integral control unit.
- Safety trip bars all round stop descent if in contact with an obstruction.
- 3-phase 380/415Vac required.



Code	Cap. kg	Platform L x W mm	Lift height mm	Lifting speed mm/sec.	Price £ each
410153DX8	1000	1300 x 820	205 - 990	20 - 25	1999.00
418491DX8	1000	1450 x 1140	205 - 990	20 - 25	2450.00
410154DX8	2000	1300 x 850	230 - 1000	30 - 40	2199.00
377925DX8	3000	1300 x 800	235 - 1010	30	2538.00

1 Low profile static powered lift table with ramp

- Low closed height, simple to operate and easy to site.
- Includes simple separate control unit.
- Anti-crush safety trip bars stop table lowering when obstructed.
- 100% welded bottom frame and integrated hydraulics.
- Supplied ramp assists loading by hand truck, pallet truck or stacker.
- Table height 860mm (raised), 85mm (lowered).
- UKCA & CE marked.



Code	Capacity kg	Platform L x W mm	Lifting speed mm/sec.	Price £ each
410156DX8	1000	1450 x 1140	25	3279.00

Air operated load levelling pallet positioner

- Self-levelling design keeps loads at an optimum working height, to eliminate bending and improve productivity.
- · Rotating ring deck helps avoid reaching and stretching.
- Compressed air operation gives more controlled (dampened) movement to the platform.
- Infinitely adjustable for varied loads by simply adding or bleeding air - no difficult changing of springs required.
- Easily transportable by fork lift truck.
- Capacity 113 - 1814kg.
- Platform height 267 - 775mm.
- Ring dia. 1092mm.
- Base L x W: 1245 x 617mm.
- · Weight 239kg.
- UKCA & CE marked.











NB. Flease note these are made to order and are therefore non-returnable.				
	Code	Price £ each		
	358034DX8	5999.00		

G Powered high lift pallet truck and work positioner

- Dual purpose manual drive electric lift pallet truck and work positioner. • Load raised at the touch of a button.
- · Stabilising bars automatically lock into place as truck lifts for easy unloading/loading.

· With slow lowering for delicate loads, and overload valve. · Nylon rollers give smooth handling.

- Capacity 1000kg.
- Lifting height: 85 800mm.
- Fork length 1190mm.
- Supplied with a 12V 63Ah battery and 12V 10Ah charger.





Code	Width over forks x L mm	Price £ each	
318030DX8	560 x 1190	2190.00	
318031DX8	680 x 1190	2275.00	