

Ladders & Steps

Step Ladders & Folding Steps

A Professional platform steps with handrails

- Extra large platform W275 x D370mm.
- Extra deep treads D95mm for comfort and security.
- High support rail with integral, foldaway work tray.
- Twin handrails with safety grips.
- Capacity: 150kg max.
- BS **EN131 Professional** compliant.
- 10 year guarantee.



Fold away tool tray

10 YEAR
GUARANTEE

150
KG



7 tread

Code	No. of treads inc. platform	Platform height mm	Closed height mm	Weight kg	Price £ each
410925DX8	3	580	1230	4.97	POA
410926DX8	4	800	1450	5.77	POA
410927DX8	5	1030	1680	6.77	POA
410928DX8	6	1250	1900	8.27	POA
410929DX8	7	1480	2130	9.27	POA

B Heavy duty platform step with handrails and tool tray

- Strong welded, ribbed aluminium frame.
- Polypropylene platform 280 x 255mm.
- Removable aluminium tool tray and handrail, self assembly required, fixings included.
- Guardrail height 600mm.
- Flanged slip resistant treads.
- Distance between steps 250mm.
- Reinforced slip resistant rubber feet.
- Capacity: 150kg. • **EN131** compliant.

5 YEAR
GUARANTEE

150
KG



Built in tool tray



Slip resistant rubber feet

Code	No. of treads inc. platform	Platform height mm	Max working height mm	Height closed mm	Width mm	Weight kg	Price £ each
397936DX8	5	1160	3200	2050	490	8	POA
397937DX8	6	1390	3430	2300	510	9	POA
397938DX8	7	1610	3660	2550	540	10	POA
397939DX8	8	1850	3890	2800	565	11	POA
397940DX8	10	2300	4350	3300	615	13.5	POA
397941DX8	12	2770	480	3800	665	16	POA

C Industrial heavy duty aluminium platform steps

- Reinforced beams and platform.
- Box-section back legs.
- Extra cross braces and 'k' straps.
- Non-slip treads with low bottom tread for greater rigidity.
- Rubber feet.
- Lightweight - easy to carry.
- Capacity: 150kg.
- **EN131-2 Professional** certified.

150
KG



Code	No. of treads inc. platform	Platform height mm	Closed H x W mm	Weight kg	Price £ each
412230DX8	4	810	1600 x 430	5.5	POA
412231DX8	5	1030	1830 x 450	6.5	POA
412232DX8	6	1250	2060 x 490	7	POA
412233DX8	7	1470	2290 x 500	8.5	POA
412234DX8	8	1690	2540 x 520	9	POA
412235DX8	10	2130	2810 x 570	9.5	POA
412236DX8	12	2570	3010 x 630	11	POA