

# Handling & Lifting Pallet Trucks



Sealed hydraulic pump unit



Tandem rear rollers and guide wheel



Rubber tyred steering wheels



## A Quicklift pallet trucks

- Max. raised height in only 5 strokes.
- Up and away in less than half the time taken with a standard truck.
- 2000kg capacity.
- Fork height lowered - 85mm.
- Fork height raised - 200mm.
- Fork width - 160mm.
- Rubber front steering wheels, tandem polyurethane rear rollers and guide wheel.

### Fork W x L - 550 x 1150mm

- Suitable for Euro, CHEP and UK sized pallets.

Code	Width over forks x L mm	Wt. kg	Price £ each
403013DX8	550 x 1150	79	339.00

### Fork W x L - 685 x 1220mm

- Suitable for CHEP and UK sized pallets.

Code	Width over forks x L mm	Wt. kg	Price £ each
403014DX8	685 x 1220	81	366.00



Three function handle with brake



Sealed hydraulic pump unit



Rear rollers with guide wheel



## B Heavy duty braked pallet trucks

- 2500kg capacity.
- Dual action brake, for safety when controlling heavy loads or parking.
- Mounted on 200mm dia. rubber steering wheels and single nylon rear rollers.
- Fork width 160mm.
- Fork height: 85 - 200mm.
- UKCA & CE marked.

### 540mm width over forks

- Suitable for Euro, CHEP and UK sized pallets.

Code	Width over forks x L mm	Wt. kg	Price £ each
388961DX8	540 x 1000	80	591.00
388962DX8	540 x 1220	81	602.00


### 680mm width over forks

- Suitable for CHEP and UK sized pallets.

Code	Width over forks x L mm	Wt. kg	Price £ each
388963DX8	680 x 1000	82	629.00
388964DX8	680 x 1220	83	642.00



Tandem nylon rear rollers, with guide wheel



Hydraulic pump unit



## C Galvanised steel pallet truck

- A fully featured, corrosion resistant pallet truck which is easy to wash down.
- Used in chemical, pharmaceutical, food and beverage industries.
- Capacity 2500kg.
- Robust monolithic hydraulic pump unit, with chrome piston rod and pressure release valve.
- Ergonomic 3D handle.
- Three position lever, with variable lowering speed control - handy when handling fragile goods.
- Tapered forks tips and entry guide rollers assist use with closed pallets.
- On 200mm dia. nylon steering wheels, and twin 82mm dia. nylon rear rollers.
- Lift height 85 - 115mm.
- Forks 525mm x 1150mm, width 150mm.
- Weight 63kg.
- CE marked.

Code	Width over forks x L mm	Price £ each
421038DX8	525 x 1150	749.00