

Premises Dehumidifiers / Heaters

A 12L Dehumidifier

- Portable unit with carry handle.
- Suitable for areas up to 15m².
- Carbon filter and ioniser for air purification. • 4 modes. • Continuous drain option; water hose provided.
- Overflow indicator and auto shut-off when full. • Auto restart/frost prevention. • 24hr timer and sleep mode. • LED control panel.
- Child lock. • Running temperature: 5 – 32°C. • H460 x W280 x D240mm.



Code	Extraction L/day	Tank capacity	Fan speeds	Power	Price £ each
406851DZ1	12	2.5 litres	2	275w	165.00

B 50L Dehumidifier

- Portable unit.
- Suitable for areas up to 115m².
- 2 modes.
- Ioniser function to purify air.
- Continuous drain option; water hose provided.
- Auto shut-off when tank is full.
- Touch control digital display with 24 hour timer.
- Frost protection.
- Environmentally friendly refrigerant R410A.
- Running temperature: 5-35°C.
- H616 x W392 x D82mm.



Code	Extraction L/day	Tank capacity	Fan speeds	Power	Price £ each
428081DZ1	50	6.0 litres	2	775w	289.00

C 20L Dehumidifier

- Mobile dehumidifier with LED display.
- Suitable for areas up to 30m².
- Touch button controls and humidity indicator light. • 3 modes.
- Dry clothes function. • Continuous drain option; water hose provided.
- Auto shut-off when tank is full.
- H600 x W355 x D200mm.



Code	Extraction L/day	Tank capacity	Fan speeds	Power	Price £ each
433269DZ1	20	5.5 litres	2	440w	220.00

D Heavy duty dehumidifiers with optional pump

- Portable low noise dehumidifier.
- Robust and reliable with epoxy coated steel cabinet.
- Hot gas defrost and adjustable humidistat.
- Includes 7.8m, clear PVC tube to remove condensation.
- Extraction: 10 litres per day.
- Airflow: 150m³/hr.
- Weight: 26kg.
- H550 x W345 x D350mm.
- 390670DZ1 fitted with hour meter and automatic condensate pump for continuous operation.



Code	Description	Price £ each
314969DZ1	Dehumidifier	547.00
390670DZ1	Dehumidifier with pump	600.00

E Industrial portable dehumidifiers

- Prevents the build-up of mildew and mould.
- Auto-defrost function if room temperature falls too low.
- Washable, activated carbon air filter.
- Connect to a drain hose for continuous operation.
- Working temperature: 5°C- 35°C.



Code	Extraction L/day	Airflow	Power w	H x W x D mm	Price £ each
424994DZ1	30	300m ³ /hr	1000/1350	680 x 620 x 410	580.00
424993DZ1	50	350m ³ /hr	750/950	660 x 610 x 400	654.00
424992DZ1	70	800m ³ /hr	420/500	1050 x 600 x 490	990.00