

D Commercial portable air conditioner 6kW

**2 YEAR
WARRANTY**

- High quality portable air conditioning unit.
- Suitable for use in offices, classrooms, workshops, warehouses - areas up to 150m³.
- Dual outlets included as standard, allows two areas to be cooled from one unit.
- Digital thermostat with auto on/off.
- Lockable castors.
- Cooling capacity: 22,179 btu/6kW.
- Airflow m³/hr: 1,198m³ (max).
- 2.5m of insulated exhaust ducting and 2 x 500mm click stop cooling duct included. Additional ducting available separately, up to 10M.
- Refrigerant: R454C - Low GWP, 95% less harmful to the environment.
- Power supply: 230v (13A).
- Weight: 92kg.
- IP Rating: IP2X.
- Noise: 65dB.
- H1086 x W526 x D774mm.



Code	Price £ each	Price £ each 2+
422417DZ1	2657.00	2551.00

E 24,000 BTU industrial portable air conditioner with timer

- Air conditioner with automatic in-built water wheel.
- Quiet operation due to adjustable fan speed and self evaporating.
- 3 speed settings.
- Energy saving sleep mode and defrosting modes.
- Condenses water whilst in cool mode.
- LED remote control included.
- 2 x 1.5m ducted exhaust hose included.
- Adjustable window mounting pane included, allows quick and easy set up.
- Built in WiFi control using the Smart Life App.
- Cooling capacity: 24,000 BTU.
- Moisture removed: 120L/day.
- H1204 x W574 x D708mm.



Code	Price £ each	Price £ each 2+
433271DZ1	1413.00	1357.00

F Commercial split air conditioner unit 7.4kW

**2 YEAR
WARRANTY**

- Water cooled.
- Suitable for server rooms and data centres, offices, classrooms, workshops, warehouses etc.
- Cooling capacity: 24,909 btu/7.4kW.
- Airflow m³/hr (main unit): 1,100m³ (max).
- Max height of outdoor unit above indoor unit: 5m.
- Units can be up to 35m apart max; 5m umbilical line supplied.
- Additional 10M umbilical hose sections available.
- Digital thermostat with auto on/off.
- Lockable castors.
- Efficient, low noise EC fan technology with speed control.
- Refrigerant: R454C - Low GWP.
- Power supply: 230v (13A).
- Weight (Indoor unit/heat exchanger): 90/23kg.
- IP Rating (Indoor/Outdoor): IP2X/IP24.
- Noise (Indoor/Outdoor): 65/64dB.
- Main unit: H1308 x W805 x D382mm.
- Heat exchanger: H530 x W555 x D340mm.



Code	Price £ each
422419DZ1	4735.00

G Commercial split air conditioner unit 14.6kW

**2 YEAR
WARRANTY**

- High quality split air conditioning unit.
- Use in offices, classrooms, workshops, warehouses and more.
- Cooling capacity: 49,476 btu/14.6kW.
- Airflow m³/hr (main unit): 2,200m³ (max). Heat exchanger: 6200m³ (max).
- Main unit and outdoor section can be up to 35m apart (with umbilical line), no need for ducting. 5m umbilical line supplied as standard.
- Additional 10M umbilical hose sections available separately, maximum overall length per unit: 35M.
- Digital thermostat with auto on/off.
- Lockable castors.
- EC fan technology with variable fan speed control to minimise noise and maximise efficiency.
- Refrigerant: R454C - Low GWP, 95% less harmful to the environment.
- Power supply: 230v (32A).
- Weight (main unit/heat exchanger): 125/50kg.
- Main unit: H1835 x W670 x D450mm.
- Heat exchanger unit: H1030 x W590 x D490mm.
- Max height of outdoor unit above indoor unit: 5m.
- IP Rating (Indoor/Outdoor): IP2X/IP24.



Code	Price £ each
422420DZ1	8090.00