

Slingsby powered Go-Far platform trucks

- Easy to operate, variable forward/reverse drive.
- Non-marking buffer and load wheels.
- Safety features include Deadman brake, and 'anti-pinning' which automatically stops the truck if accidentally reversed into the operator's body.
- Full charge provides a working day's use under normal conditions.
 Quiet 24V DC system.
 Capacity 450kg UDL.
 Easy to clean slip
- resistant plastic deck (zinc plated steel on 425068DX8 & 426497DX8). • Deck height 345mm. • Overall height: 1030mm (429800DX8 is
- 1275mm) Complies with 2004/108/EC and 2006/42/EC (as amended). 429800DX8 features hinged lockable side gates and half hinged lid. Optional weather proof polyester-coated tiller cover, with clear PVC panel for a full view of the electronic display and controls, elasticated cuffs to keep hands warm and dry, and taped seams.

Code	Configuration	Deck	Price £
	-	W x L mm	each
307952DX8	Single handle only	600 x 1060	3572.00
307957DX8	2 ends and 2 detachable sides	600 x 1060	3941.00
394480DX8	With load level container	600 x 1060	3995.00
429800DX8	Tall 2-tier lockable security cage	600 x 1060	4599.00
394481DX8	With long basket	600 x 1060	4195.00
426497DX8	4-sided cage with split detachable side	630 x 1040	4399.00
425068DX8	Large 4-sided cage with split detachable side	655 x 1260	4531.00
426550DX8	Tiller cover		64.00



Go-Far with single handle



Go-Far with 2 ends and 2 detachable sides



Go-Far with long basket



Go-Far with load level container



Go-Far with 4-sided cage and split detachable side



Weather-proof tiller cover



Go-Far with tall 2-tier lockable security cage



Go-Far with large 4-sided cage inc. split detachable side

Information

The option of taking out a maintenance and service contract using our fully trained engineers is available - please ask for details.