

G Digital tally counter

• 15mm LCD display with backlight.

· Large countup/down buttons, adds and subtracts 0 to 9,999.



 Count confirmation bleep or silent operation.





Code	Price £ each 1 - 4	Price £ each 5+
408185DX8	11.49	10.99

Tally counter

- Hand held manual counter.
- · Zero reset facility can be removed to prevent unauthorised tampering.



Code	Description	Price £ each 1-2	Price £ each 3+
309892DX8	Hand held	10.49	9.99

Economy stopwatch

- Big digit display. 1/100 second precision (for the first 30 minutes) with lap counter.
- Calendar and time (12 / 24 hour format).
- Hourly chime. Daily alarm.
- Case size: 64 x 53 x 19mm.
- · Battery and neck cord included.



Code	Price £ each 1-2	Price £ each 3+
347598DX8	6.79	6.49

2 YEAR

GIIARANTE

NEW

Bench process stop-clock timer

- 15mm LCD display.
- 30ppm guartz crystal with a fixed calibrated capacitor of 27pF for hi-accuracy timing.
- Impact-resistant ABS case with non-slip rubber feet for stability. • Quick and easy press-button for



sockets. H80 x W100 x D105mm Battery in	PARSON COMMON	Stormur
Code	Price £ each 1 - 4	Price £ each 5+

L STOP-CLOCK

Code	Price £ each 1 - 4	Price £ each 5+
408186DX8	12.49	11.99

Legionnaires' standard water temperature thermometer kit

- Monitor water supply temperatures for prevention of Legionella growth.
- Easy-to-use therma 1 industrial thermometer with K thermocouple sensor.

• Temperature range: -99.9 - +1372 °C with a 0.1 °C or 1 °C resolution.

Accuracy to ±0.4°C ±0.1%.

• Immersion probe, ribbon surface temperature probe for surface of pipes and tanks and heavy duty PTFE wire probe for difficult to reach areas Supplied with 1.5 volt AAA

batteries - 10000hrs/5yr battery life.

• ABS protective PVC zip pouch with Biomaster Antimicrobial technology.

 FREE traceable certificate of calibration.

• 2 year guarantee

Code	Price £ each	
428330DX8	114.00	

Inspection borescope with

• Remote video inspection device.

colour monitor

- 60mm (2.4") TFT colour display 480 x 234 pixels. • 1m flexible gooseneck with waterproof, IP-67, 9mmØ camera head.
- · Gooseneck can be preformed to a configured shape. • Clip-on mirror, magnet and hook attachments for object retrieval.
- Glare free close up and wide field of view (36°). • 4 Adjustable dual, bright white LED lights. • Requires 4 x AA batteries.



Code	Description	Price £ each
385870DX8	Borescope	115.00
385871DX8	1m extension	35.49

M Legionnaires' premium water temperature thermometer kit

• To monitor water supply temperatures for the prevention of Legionella growth. • 12mm LCD display.

• Easy-to-use therma 1 industrial thermometer with K thermocouple sensor. • Temperature range: -99.9 - +1372 °C with a 0.1 °C or 1 °C resolution. • Accuracy to ±0.4 °C ±0.1%.

• Penetration temperature probe to record the temperature of tap water, ribbon Surface temperature probe for surface of pipes and tanks and wire probe for areas that are difficult to reach. • Water Resistant Countdown Timer.

Supplied with 1.5 volt AAA batteries - 10000hrs/5yr battery life.

• Mini tub of 35 Probe Wipes. • ABS carrying case with Biomaster Antimicrobial technology.

FREE traceable certificate of calibration.

• 2 year quarantee.

· Employers or persons in control of premises are legally responsible for testing for Legionella.



