

Wheels & Castors Castors – Light & Medium Duty

A Polypropylene plate fixing castor

- Plain bearings.
- Fixing centres: 38x38mm - 48x48mm M6 (Ø50/75mm wheels), or 52x52mm - 58x58mm M8 (Ø100/125mm wheels).



Swivel (A1)

Swivel with total-stop brake (A2)

Code	No.	Wheel dia. mm	Tread width mm	Top plate size mm	Fitted height mm	Load cap. kg	Price £ each
384349DX8	A1	50	20	60 x 60	69.5	50	2.65
384350DX8		75	25	60 x 60	100	70	4.80
384351DX8		100	27	76 x 76	134	80	8.55
384352DX8		125	27	76 x 76	155.5	100	9.95
384353DX8	A2	50	20	60 x 60	69.5	50	4.25
384354DX8		75	25	60 x 60	100	70	5.85
384355DX8		100	27	76 x 76	134	80	10.49
384356DX8		125	27	76 x 76	155.5	100	12.99

B Polypropylene bolt hole fixing castor

- Plain bearings.
- Fixing hole: M10 (Ø50/75mm wheel), M12 (Ø100/125mm wheel).



Swivel (B1)

Swivel with total-stop brake (B2)

Code	No.	Wheel dia. mm	Tread width mm	Fitted height mm	Load cap. kg	Price £ each
384357DX8	B1	50	20	68	50	3.20
384358DX8		75	25	98	70	5.30
384359DX8		100	27	131.5	80	9.10
384360DX8		125	27	153	100	10.10
384361DX8	B2	50	20	68	50	4.25
384362DX8		75	25	98	70	5.85
384363DX8		100	27	131.5	80	10.49
384364DX8		125	27	153	100	12.99

C Polypropylene plate fixing twin wheel castor

- Plain bearings.
- Top plate size 60 x 60mm.
- Fixing centres 38x38mm to 48x48mm, M6.



Swivel (C1)

Swivel with total-stop brake (C2)

Code	No.	Wheel dia. mm	Tread width mm	Fitted height mm	Load cap. kg	Price £ each
384991DX8	C1	50	20 x 2	71	80	5.35
384992DX8		75	25 x 2	103	100	9.60
384993DX8	C2	50	20 x 2	71	80	6.40
384994DX8		75	25 x 2	103	100	12.49

D Polypropylene bolt hole fixing twin wheel castor

- Plain bearings.
- M10 fixing hole.



Swivel (D1)

Swivel with total-stop brake (D2)

Code	No.	Wheel dia. mm	Tread width mm	Fitted height mm	Load cap. kg	Price £ each
384995DX8	D1	50	20 x 2	71	80	4.80
384996DX8		75	25 x 2	100	100	9.05
384997DX8	D2	50	20 x 2	71	80	6.40
384998DX8		75	25 x 2	100	100	12.49

E TPR tyred, nylon centre plate fixing castor

- Thermoplastic rubber (TPR) tread.
- Plain bearings.
- Fixing centres: 38x38mm to 48x48mm M6 (Ø50/75mm wheels), or 52x52mm to 58x58mm M8 (Ø100/125mm wheels).



Swivel (E1)

Swivel with total-stop brake (E2)

Code	No.	Wheel dia. mm	Tread width mm	Top plate size mm	Fitted height mm	Load cap. kg	Price £ each
384365DX8	E1	50	20	60 x 60	69.5	50	3.70
384366DX8		75	25	60 x 60	100	70	4.35
384367DX8		100	27	76 x 76	134	80	8.55
384368DX8		125	27	76 x 76	157	100	9.10
384369DX8	E2	50	20	60 x 60	69.5	50	4.80
384370DX8		75	25	60 x 60	100	70	5.95
384371DX8		100	27	76 x 76	134	80	9.99
384372DX8		125	27	76 x 76	157	100	10.99

F TPR tyred, nylon centre bolt hole fixing castor

- Thermoplastic rubber (TPR) tread.
- Plain bearings.
- Hole fixing: M10 (Ø50/75mm wheel), M12 (Ø100/125mm wheel).



Swivel (F1)

Swivel with total-stop brake (F2)

Code	No.	Wheel dia. mm	Tread width mm	Fitted height mm	Load cap. kg	Price £ each
384373DX8	F1	50	20	68	50	3.75
384374DX8		75	25	98	70	5.85
384375DX8		100	27	131.5	80	8.00
384376DX8		125	27	154.5	100	9.05
384377DX8	F2	50	20	68	50	4.80
384378DX8		75	25	98	70	6.90
384379DX8		100	27	131.5	80	8.85
384380DX8		125	27	154.5	100	9.99