

Handling & Lifting Lift Tables, Stackers & Work Positioners

A Manual and powered mobile lift tables

- Manoeuvrable and easy to use.
- Hydraulic foot pump or battery powered operation.
- Overload and lowering speed control valves.
- Conforms with BS EN1570, with operating instructions and test certificate.
- On non-marking polyurethane tyred or nylon castors, 2 fixed, 2 swivel with toe guards (1 braked).
- Battery powered models feature remote control push button up/down operation, 12V traction battery with plug-in charger, and safety cut-off bar to stop the platform from lowering if obstructed.
- UKCA & CE marked.



Manual single lift



Manual double lift



Battery powered double lift



Battery powered triple lift

Capacity kg	Platform height mm	Platform W x L mm	Lift type	Manual lift Code	Price £ each	Battery powered lift Code	Price £ each
125	430 - 1420	500 x 840	Double	388145DX8	1543.00	375165DX8	4244.00
300	335 - 840	500 x 840	Single	325974DX8	1322.00	375166DX8	3851.00
	295 - 1350	590 x 840	Double	325973DX8	1726.00		
450	295 - 1550	610 x 1030	Double	388146DX8	1919.00	375167DX8	4629.00
500	340 - 900	610 x 1030	Single	388144DX8	1518.00	375169DX8	4434.00
	490 - 1900	840 x 1350	Double	388150DX8	2892.00	375168DX8	5502.00
	655 - 2900	840 x 1350	Triple	388152DX8	4906.00	375170DX8	6998.00
800	360 - 1050	840 x 1350	Single	388147DX8	2968.00	375172DX8	4907.00
	490 - 1900	840 x 1350	Double	388151DX8	3864.00	375171DX8	5953.00
1000	360 - 1050	1000 x 2000	Single	388149DX8	3440.00	375163DX8	5806.00
1250	360 - 1050	840 x 1350	Single	388148DX8	3566.00	375164DX8	5655.00

B Medium duty mobile lift table

- Durable galvanised chassis and platform, facilitates cleaning.
- Larger wheels and shorter wheel base - easier to manoeuvre and roll over uneven ground.
- Hand operated controls - easier to adjust giving increased control of lowering motion.
- Capacity 500kg.
- Overall L x W: 1150 x 650mm.
- Weight 75kg.



Code	Lift height mm	Platform L x W mm	Price £ each
410152DX8	320 - 920	900 x 600	823.00

C Light duty mobile lift table

- Load capacity 150kg.
- Fold down flat handle for easy transportation.
- UKCA & CE marked, and complies with BS EN1570.
- Manual hydraulic lift, operated by foot pump - typical lifting time 14s.
- Lowering speed control valve.
- On two fixed and two swivel non-marking castors, fitted with total-stop foot brakes.
- Weight 41kg.



NB. Please note these are made to order and are therefore non-returnable.

Code	Lift height mm	Platform W x L mm	Overall W x L mm	Price £ each
325972DX8	255 - 780	450 x 760	450 x 990	1125.00