

Three section ladder.Welded aluminium construction and rigid corrugated treads.

• Interlock system to prevent uncontrolled splaying.

- Weather resistant straps.
- · Slip resistant feet.

• Stabiliser bar with non slip footpads.

 Can be used as an extension ladder, extended free standing ladder, step ladder or stair step ladder.

Capacity:150kg.

 EN131 Non Professional, and TUV certified.





Code	Height extended m	Height closed m	No. of rungs	Weight kg	Price £ each
404984DX8	4.0	1.89	3 x 7	11.8	P0A
404985DX8	5.6	2.4	3 x 9	14.5	POA
404986DX8	7.2	2.95	3 x 11	17.6	P0A
404987DX8	8.8	3.47	3 x 13	24.0	P0A
404988DX8	9.6	3.75	3 x 14	26.2	P0A

Telescopic aluminium ladders

- Aluminium construction with anodised finish.
- · Soft close system.
- Rung by rung height adjustment.
- Automatic engagement when extending the ladder.
- Wear resistant, anodised uprights.
- · Corrugated treads.
- Compact and easy to store.
- Capacity:150kg
- Complies with EN131-6







• Heavy duty aluminium extension ladders

- Aluminium construction.
- Industry leading 35mm corrugated treads for strength and durability.
- Rungs orientate flat when erected at correct climbing angle.

Heavy duty galvanised locking catch.

Deep serrated rubber feet provide greater grip.
Stabiliser as standard on 3m+ options.

Stabiliser as standard on 3m+ options.
Wall wheels as standard on 6m+ options.

Capacity:175kg

• EN131 Non professional compliant.

• Stress tested and complies to 20% higher loads than BS EN131-2:2010 + A2:2017.















2 Section

Code	Length extended m	Length closed m	No. of rungs	Weight Kg	Price £ each
418290DX8	4	2.5	2 x 9	12.1	P0A
418291DX8	5	3	2 x 11	15.5	P0A
418292DX8	6	3.5	2 x 13	18	P0A
418293DX8	7	4	2 x 15	23.7	POA
418294DX8	8	4.5	2 x 17	28.9	POA
418295DX8	9	5	2 x 19	31.9	POA
418296DX8	10	5.5	2 x 21	34.7	POA

3 Section

0 0000.0						
Code	Length extended m	Length closed m	No. of rungs	Weight Kg	Price £ each	
418297DX8	5.5	2.5	3 x 9	23.4	P0A	
418298DX8	7	3	3 x 11	27.5	POA	
418299DX8	8.5	3.5	3 x 13	34.6	P0A	
418300DX8	10	4	3 x 15	39.3	POA	