

Handling & Lifting Forklift Attachments

A Fork extension sleeves

- Extends forks to lift longer loads.
- Toes profiled and chamfered for ease of use.
- Smooth, fully plated underside.
- Corrosion resistant safety heel pins.
- Capacity / pair @ half length: 2000kg (standard duty), 4000kg (heavy duty), 6000kg (extra heavy duty).
- Fully certified.
- Painted black.
- Supplied in pairs.
- UKCA & CE marked.

Information

On standard duty, length of extension not to exceed 1.25 x length of fork. On heavy duty, length of extension not to exceed 1.5 x length of fork. Maximum thickness of forks 60mm. For use with counterbalanced fork lift only.

Length mm	Centre of gravity mm	Min. fork length mm	Standard duty fork width 100mm		Heavy duty, fork width 125mm		Extra heavy duty fork width 150mm	
			Code	Price £ pair	Code	Price £ pair	Code	Price £ pair
1372	686	823	373408DZ1	341.00	373428DZ1	370.00		
1525	762	915	373409DZ1	367.00	373429DZ1	378.00	435931DZ1	393.00
1829	914	1100	373410DZ1	387.00	373430DZ1	404.00	435934DZ1	427.00
1981	990	1200	373404DZ1	398.00	373431DZ1	421.00	435935DZ1	447.00
2134	1067	1300	373411DZ1	419.00	373405DZ1	424.00	435936DZ1	453.00
2438	1219	1500	373426DZ1	436.00	373406DZ1	464.00	435937DZ1	487.00



B Fork mounted 1100L wheelie bin lifter & tipper

- Ensures the safe lifting, movement and emptying of wheelie bins which are equipped with side trunnions.
- Operated via gearbox and a 6M endless chain for safe use from low levels.
- Constructed with zinc plated twist screws to ensure safe attachment to forklift trucks.
- Bright orange painted finish for clear visibility and safety.
- Safe working load: 600kg.
- Ratchet tensioner strap to leading edge.
- Max fork section: 150 x 60mm.
- Centre of Gravity: 1240-1410mm.



NEW

UK
MADE

Code	Price £ each
435919DZ1	4050.00



C Load protection shock absorber

- Help to reduce damage to fragile loads when being loaded/unloaded by forklift trucks.
- Simply attach to the face of the fork and is magnetically held in place.
- Designed for best use where load in uneven as IDSA 3mm rubber fingers mould to the load to increase protection and reduce damage to goods.
- Temperature range -140 – 100 degrees Celsius.
- 30mm lost load centre.
- Choice of lengths.
- Two required per forklift.

NEW

Code	Length mm	Price £ each
435897DZ1	400	159.00
435898DZ1	420	219.00
435899DZ1	450	224.00
435900DZ1	540	251.00

N.B. Price is for a single item.



D Load buffer

- Load buffer is designed to reduce damage to fragile loads from the fork back when being unloaded/loaded.
- Simply attach to the face of the fork and is magnetically held in place.
- 25mm thick encapsulated foam pads.
- Can be easily removed/placed between trucks on one site.
- Bright orange painted finish for clear visibility and safety.
- Choice of lengths suitable for a variety of fork sections.

NEW

Code	Length mm	Max. fork section mm	Price £ each
435958DZ1	460	80 x 50	404.00
435959DZ1	460	100 x 50	462.00
435960DZ1	560	100 x 50	484.00
435961DZ1	560	130 x 60	528.00
435962DZ1	720	150 x 60	557.00

N.B. Price is for a single item.

