



Codes in Green
Faster Delivery

D Slingsby powered Go-Far™ platform trucks

- Easy to operate, variable forward/reverse drive.
- Non-marking buffer and load wheels.
- Safety features include Deadman brake, and 'anti-pinning' which automatically stops the truck if accidentally reversed into the operator's body.
- Full charge provides a working day's use under normal conditions.
- Quiet 24V DC system.
- Capacity 450kg UDL.
- Easy to clean slip resistant plastic deck (zinc plated steel on 425068RN6 & 426497RN6).
- Deck height 345mm.
- Overall height: 1030mm (429800RN6 is 1275mm)
- Complies with 2004/108/EC and 2006/42/EC (as amended).
- 429800RN6 features hinged lockable side gates and half hinged lid.
- Optional weather proof polyester-coated tiller cover, with clear PVC panel for a full view of the electronic display and controls, elasticated cuffs to keep hands warm and dry, and taped seams.

Code	Configuration	Deck W x L mm	Price € each
307952RN6	Single handle only	600 x 1060	5433.00
307957RN6	2 ends and 2 detachable sides	600 x 1060	6079.99
394480RN6	With load level container	600 x 1060	8186.00
429800RN6	Tall 2-tier lockable security cage	600 x 1060	6983.00
394481RN6	With long basket	600 x 1060	6878.00
426497RN6	4-sided cage with split detachable side	630 x 1040	6678.00
425068RN6	Large 4-sided cage with split detachable side	655 x 1260	6879.99
426550RN6	Tiller cover		95.10



Go-Far™ with single handle



Go-Far™ with 2 ends and 2 detachable sides



Go-Far™ with load level container



Go-Far™ with tall 2-tier lockable security cage



Go-Far™ with 4-sided cage and split detachable side



Go-Far™ with large 4-sided cage inc. split detachable side



Go-Far™ with long basket



Weather-proof tiller cover

Information



The option of taking out a maintenance and service contract using our fully trained engineers is available - please ask for details.

Handling & Lifting