

I Plastic rotary pump

- Reverse rotary action. • For weak acids, alkalis and salts, some organic solvents, water & all petroleum products.
- Polypropylene body. • Phenolic vanes, Viton seals and polyethylene gaskets.
- 2" BSP barrel adaptor.
- 3 piece riser tube for 210L drums. • 2 piece outlet spout, threaded 3/4" BSP ends.



Code	Flow rate ltrs/min.	Inlet/outlet Ø mm	Wt. kg	Price € each
323021RN6	35	30 / 25	2.9	151.00

J Metal rotary pumps

- Cast iron body, sinter steel mechanism.
- Nitrile rubber seals.
- 2" BSP barrel adaptor.
- Rigid riser tubes to suit 210 ltr. drums.
- Suitable for oil, diesel, kerosene & anti-freeze.



Code	Flow rate ltrs/min.	Outlet tube Ø mm	Price € each
331675RN6	16	20	64.05
331677RN6	25	23	115.00

K High flow metal rotary pumps

- Twin impellers.
- Die-cast alloy and aluminium body.
- Suitable for petrol, diesel, paraffin and very light oil.
- 2" BSP barrel adaptor.
- Rigid riser tube to suit 210L drums.
- Inlet Ø30mm, outlet Ø30mm (Ø12mm 319828RN6).
- Optional reversible rotary action.



Code	Description	Hose	Flow rate ltrs/min.	Price € each
319827RN6	Standard	PE	100	368.00
319828RN6	Reversible	Nylon	50	453.00

L AdBlue® IBC drain kit and nozzle

- For draining liquids.
- Kit contents: latching trigger nozzle, IBC adaptor and 3m hose.
- Also use with petrol, diesel, light oils, weaker acids and alkalis. • Max. flow rate 30 ltrs/min.
- Swivel hole fitting. • Latching trigger nozzle also sold separately. • Inlet/outlet Ø: 20mm.



Kit

Code	Description	Price € each
396948RN6	Kit	102.00
396945RN6	Nozzle only	48.14

M 230Vac / 12Vdc Electric drum pump

- Suitable for 210 ltr. drums.
- 230Vac adaptor & 12V battery clips.
- Max. liquid viscosity 100cst.
- Built-in fuse protection.
- Telescopic riser & stainless steel filter.
- With 2" BSP adaptor, 2m hose and manual dispensing nozzle with spout.
- CE marked.



Code	Price € each	Price € each 2+
417384RN6	467.00	455.00

N Electric heavy oil pump

- Suitable for oils and lubricants including waste oil. • Rotary vane, self-priming, with by-pass. • Flange mounted - can be wall mounted or used portably. • 3/4" BSP female inlet and outlet. • IP55 rated.
- Hoses and wall mounting bracket available.



Code	Voltage Vac	Flow rate ltrs/min.	Wt. kg	Price € each
330584RN6	230	30	13.4	1009.99

N.B. NOT for use with petrol or flammable liquids.

O 1:1 Pneumatic barrel pumps

- For low/medium viscosity oils 100cSt / SAE10-30, mineral & synthetic motor oils, antifreeze, transmission fluid.
- Riser tube suitable for 210L drums c/w 2" BSP barrel adaptor.
- Inlet pressure 140PSI max. • Outlet pressure 8 bar, 20 - 120 PSI.
- Flow rate 30 LPM. • 400331RN6 is fitted with 2m reinforced nylon hose & bent tip steel spout. • Inlet 1/4" BSPF, outlet 1/2" BSPM.
- Air connectors not supplied. • N.B. Do not use with petrol, diesel or fuel oils.



Pump
with hose

Code	Description	Price € each
396949RN6	Pump only	379.00
400331RN6	Pump with 2m hose	379.99

P 3:1 Pneumatic barrel pumps

- For low/medium viscosity oils 100cSt / SAE10-30, mineral & synthetic motor oils, antifreeze, transmission fluid. • Riser tube length suitable for 210 litre barrels c/w 2" BSP barrel adaptor.
- Max. air inlet pressure 100PSI.
- Outlet pressure 168 bar, 2100 PSI.
- Flow rate 10 LPM. • 400335RN6 is fitted with 4m reinforced nylon hose & oil control nozzle.
- Inlet 1/4" BSPF, outlet 3/8 BSPM.
- Air connectors not supplied.
- N.B. Do not use with petrol, diesel or fuel oils.



Pump with hose
& nozzle

Code	Description	Price € each
400334RN6	Pump only	624.00
400335RN6	Pump with 4m hose & nozzle	842.00