

A Whirling hygrometers

- Hand powered relative humidity measuring device (%RH). • Rotate to provide adequate and consistent ventilation of the bulbs.
- Environmentally friendly blue thermometer tubes with LO-tox™ filling. • Similar accuracy as mercury but with clearer legibility.
- Range: -5 to +50°C. • Accuracy: +/- 1°C.
- Resolution: 0.5°C.



Compact whirling hygrometer

- Compact measurement tube.
- Incorporates 'slide rule' type calculator to determine % RH. • Main body slides into the handle when not in use.
- L210 x W36 x D16mm.

Code	Price € each 1-2	Price € each 3+
371873RN6	64.05	62.45

Whirling hygrometer with folding handle

- Protective carry case, calculator chart and 2pcs spare wicks all included.
- L230 x W130 x D23 mm.

Code	Price € each
429159RN6	139.00

D USB data logging thermo-hygrometer

- Measures and stores up to 16,350 temperature (-40°C to +70°C) and humidity (0 to 100%RH) readings.
- Measurement °C or °F.
- Large 29mm LCD display.
- USB interface for set-up and data transfer to PC or laptop. • Analysis software with graphical display of data.
- Impact-resistant ABS and rubber moulded case, wall holder, padlock, software, USB cable and battery all included.
- H92 x W47 x D30mm.



Rubber moulded case, wall holder & padlock



Code	Price € each 1-2	Price € each 3+
394316RN6	116.00	113.00

B Thermo-hygrometer

- Simultaneously displays both the temperature and the humidity.
- Indicate and record maximum and minimum temperature and humidity readings.
- Range: 0 to 50°C and 10 to 95% relative humidity utilising the internal sensors.
- Batteries: 1.5 volt AAA (supplied).
- Dimensions: H100 x W110 x D20 mm.
- Weight: 135g.



Code	Price € each 1-2	Price € each 3+
387678RN6	19.09	18.65

C Large thermo-hygrometer

- Simultaneous display of humidity and temperature ideal for environmental monitoring of clean rooms, laboratories, computer rooms and storage rooms.
- 50 x 63mm LCD display. • Range: -10 to 50°C x 0.1°. • 30 to 90% RH x 1%.
- Displays temperature in °C or °F.
- 5 Level comfort indicator. • Min/max memory for both temperature and humidity.
- Impact-resistant ABS case with flip out desk stand for free standing applications and key-way for wall mounting.
- H135 x W100 x D20 mm.
- Battery included.



Code	Price € each 1 - 4	Price € each 5+
408184RN6	34.84	33.99

E Velocity volume thermo anemometer

- Measures air velocity from 0.4-30 m/s in multiple units including m/sec, ft/min, mph, km/hr and knots. • Measures airflow volume in m³/min (CMM) or ft³/min (CFM). • Measures temperature in °C or °F. • Dual display shows air velocity and temperature simultaneously on a backlit 35 mm LCD. • Features data hold, minimum/maximum hold and 10-second average function. • Supplied with soft carry case and battery and backed by a 2-year warranty.



Code	Price € each 1-2	Price € each 3+
389943RN6	118.00	115.00

F Waterproof anemometer

- Pocket sized anemometer with 14mm LCD display. • Provides highly accurate air velocity readings: 0.4 to 40m/sec.
- Measurement units: m/sec, ft/min, mph, km/hr, knots or Beaufort force.
- Data hold freezes displayed readings.
- Dust-tight and waterproof to 1m to IP-67 (IEC standard 60529).
- Can be submerged for up to 30 minutes.
- High precision Zytel bearings and a light weight impeller.
- Shock-resistant.
- Battery life approx 300 hours.
- Designed to float, perfect for use in wet environments.
- Supplied with lanyard and battery.



Code	Price € each
428370RN6	237.00