

G Manual or auto range sound level meter

- Accurate measurement of sound levels for workplace, industrial and environmental monitoring.
- Selectable A and C frequency weighting with fast and slow response times.
- Clear backlit LCD display with easy-to-read digits and function indicators.
- Manual or auto ranging models available, covering typical 30–130 dB ranges.
- Min, max and data hold functions for quick review of readings.
- Wind muffler supplied for improved accuracy during outdoor use. • Tripod mount and calibration certificate options available on selected models.

**2 YEAR
GUARANTEE**



Code	Description	Price € each	Price € each 3+
389941RN6	Manual/Auto	104.00	101.00
394119RN6	Precision	342.00	333.00

H Sound level and temperature meter

- Has a wide dynamic range and gives virtually instant readings. • Ideal for quick and easy environmental sound level checks.
- Features an accuracy of ± 2 dB, a fixed 'A' frequency rating, and the choice of fast or slow time weightings.
- Also features the environmental temperature on its Hi-contrast colour LCD display as well as min/max and data hold functions.
- Single measurement range: 30 to 130 dB.
- Hi-range >100dB, Lo-range <100dB.
- 0.1 dB Resolution, accuracy 2dB (94dB @ 1KHz). • Temperature -20° to +70°C, accuracy $\pm 1.5^\circ\text{C}$.
- Supplied with wind muffler and battery.



Code	Price € each
408153RN6	76.24

I Professional LED light meter

- Professionally calibrated LED light meter compliant with JIS C 1609-1993 for accurate daylight spectrum measurement.
- Measures illuminance in lux or footcandles with a wide range up to 400,000 lux.
- Selectable light source mode for LED and standard lighting measurements.
- Large backlit LCD with bargraph, data hold and min/max/average functions.
- Supplied with sensor on 1.5 m coiled cable, protective lens cap, carry pouch and batteries.



Code	Price € each 1-2	Price € each 3+
402615RN6	237.00	231.00

J Data logging light meter

- Data logging light meter with USB interface.
- Measures both Lux and Foot candles. • Range: upto 400,000 Lux, 40,000 FC.
- Memory stores 99 recallable readings. • Records up to 16,000 readings with sampling rates and time set up by the user. • Dimensions: H203 x W75 x D50 mm.



Code	Price € each
380530RN6	257.00

K 4-in-1 environment meter

- Measures sound levels, light levels, % RH and temperature.
- Range: Sound 35 to 130dB, Lux 0 to 20,000 lux, % RH 25% to 95%, Temperature -20° to +750°C.
- Accuracy: Sound ± 3.5 dB, Lux $\pm 5\% + 10$ dgts, % RH 5% RH, Temperature $\pm 3.5\%$ rdg $\pm 2^\circ\text{C}$.
- Power: 1 x 9V PP3 alkaline battery (LR-61). • Dimensions: H250 x W63.8 x D40mm.
- Weight 250g.



Code	Price € each 1-2	Price € each 3+
402618RN6	187.00	182.00

L 5 in 1 environment meter

- 5-in-1 environmental meter measuring sound level, light, airflow, humidity and temperature.
- Supports workplace health and safety monitoring and compliance.
- Auto-ranging sound measurement with 'A' frequency weighting and cosine-corrected lux sensor.
- 70 mm vane for airflow and semiconductor probes for humidity and temperature in °C or °F.
- Supplied in a briefcase-style carry case with probes, wind muffler and battery.



Code	Price € each 1-2	Price € each 3+
394121RN6	273.00	266.00