

Packaging & Mailroom Strapping

A Woven polyester strapping

- A strong, safer and greener alternative to steel.
- Does not disintegrate, split or jam in use.
- Does not rust.
- Can be re-tightened if required.
- 78mm cardboard core diameter.
- Colour: white.



Code	Strap W mm	Roll L m	Breaking strain kg	Price € per reel
323497RN6	13	1100	375	72.10
426269RN6	16	600	600	76.09
323498RN6	16	850	450	94.74
426270RN6	19	500	725	83.04
323499RN6	19	600	550	67.34

B Polyester strapping sealers

- For extruded polyester strapping and compression seals.



Code	Description	Price € each	Price € each 2+
308338RN6	12mm Sealer	76.70	74.79
308339RN6	16mm Sealer	66.94	65.29

C Extruded polyester strapping

- Embossed polyester strapping suitable for manual or automatic processes.
- High strength and elasticity for quality load retention and easy application.
- Supplied on cardboard reels for handling convenience.
- 100% recyclable including core.
- Does not damage products during transit or storage.
- Suitable for heavy consignments and stays firm over time.
- Breaking strength: 350kg (330-370kg).
- 12 x 0.7mm x 2000 metre.



Code	Price € each 1-2	Price € each 3+
435642RN6	147.00	143.00

D Versatile heavy duty tensioner

- Suitable for use with polypropylene, woven polyester, composite polyester and extruded polyester (PET).
- Tensions strap width up to 19mm.



Code	Price € each
428932RN6	399.99

E Extruded polyester (PET) strapping

- Extruded polyester offers high strength and elasticity.
- Thickness: 0.7mm (426271RN6 is 0.55mm).
- Choice of core type and strap width.
- Cardboard core dims: 406 x 150mm.
- 100% recyclable.
- Manufactured with at least 30% recycled material.



Plastic
Cardboard

Code	Type	Strap width mm	Breaking strain kg	Strap thickness mm	Core type	Reel length m	Price € per reel
408245RN6	Embossed	15.5	440	0.70	Cardboard	1,750	144.00
426271RN6	Embossed	12.5	270	0.55	Plastic	1,600	107.00
426272RN6	Embossed	15.5	440	0.70	Plastic	1,200	115.00

F Polyester strapping tensioner

- For woven and composite polyester strapping up to 19mm.
- Painted aluminium alloy.
- Dimensions: 268 x 69 x 136mm.
- Tensioning handle length: 237mm.
- Min./max. strap width: 9/19mm.
- Min./max. strap thickness 0.6/1.2mm.
- Maximum tension: 200kg.



Tension & cutting tool

Code	Price € each
322357RN6	67.74