

C Powered work platform with scissor lift

- For indoor or outdoor use with firm, level surfaces.
- Compact dimensions for space efficient storage.
- High angle steering provides excellent manoeuvrability.
- Variable speed motor extends battery life by using only the energy needed to do the work.
- Ergonomic joystick control operates from the platform or the ground.
- Extending platform increases usable working space.
- Power to platform - allows operator to use electrically powered work tools on the platform.
- Power source; 24V (four 6V Ah batteries) with automatic charger, 110 or 240V - please state requirement at time of order.

2 YEAR
GUARANTEE



Easy to
manoeuvre

Up to
454KG

Code	Platform height max. m	Working height m	Capacity kg	Platform external L x W m	Platform L (extended) m	Overall L x W x H (stowed) m	Weight kg	Price € each
358144RN6	5.79	7.79	227	1.63 x 0.74	2.54	1.83 x 0.813 x 2.11	1498	21149.00
358145RN6	7.92	9.8	454	2.26 x 1.15	3.18	2.41 x 1.17 x 2.26	2447	29634.00
405503RN6	9.5	11.5	318	2.26 x 1.15	3.18	2.41 x 1.17 x 2.39	2812	34404.00

N.B. It is recommended that users of these lifts receive IPAF operator training - details and prices on request.



D Powered drivable work platform

- Compact base; fits into most passenger lifts and rolls through standard doorways.
- Zero turning radius provides maximum manoeuvrability.
- Alarm sounds on descent and if tilted whilst extended.
- Forklift pockets (630 x 130mm) for transport by forklift.
- Stowed length: 1350mm.
- Platform L880 x W750mm.
- Ground clearance: 63.5mm.
- Power source: 24V (four 6V 225Ah batteries) with automatic charger.
- Indoor use only.



2 YEAR
GUARANTEE

Code	Load capacity kg	Working height metres	Platform height metres	Stowed height metres	Width metres	Weight kg	Price € each
358142RN6	227	6.47	4.47	1.57	0.75	994	23147.00
358143RN6	159	8.07	6.07	1.98	0.80	1111	24651.00

N.B. It is recommended that users of these lifts receive IPAF operator training - details and prices on request.