

Handling & Lifting Forklift Attachments

A Fork extension sleeves

- Extends forks to lift longer loads.
- Toes profiled and chamfered for ease of use.
- Smooth, fully plated underside.
- Corrosion resistant safety heel pins.
- Capacity / pair @ half length: 2000kg (standard duty), 4000kg (heavy duty), 6000kg (extra heavy duty).
- Fully certified.
- Painted black.
- Supplied in pairs.
- UKCA & CE marked.

Information

On standard duty, length of extension not to exceed 1.25 x length of fork. On heavy duty, length of extension not to exceed 1.5 x length of fork. Maximum thickness of forks 60mm. For use with counterbalanced fork lift only.

Length mm	Centre of gravity mm	Min. fork length mm	Standard duty fork width 100mm		Heavy duty, fork width 125mm		Extra heavy duty fork width 150mm	
			Code	Price € pair	Code	Price € pair	Code	Price € pair
1372	686	823	373408RN6	521.00	373428RN6	565.00		
1525	762	915	373409RN6	559.99	373429RN6	577.00	435931RN6	599.99
1829	914	1100	373410RN6	591.00	373430RN6	617.00	435934RN6	652.00
1981	990	1200	373404RN6	607.00	373431RN6	643.00	435935RN6	682.00
2134	1067	1300	373411RN6	639.00	373405RN6	647.00	435936RN6	691.00
2438	1219	1500	373426RN6	665.00	373406RN6	708.00	435937RN6	743.00



B Fork mounted 1100L wheelie bin lifter & tipper

- Ensures the safe lifting, movement and emptying of wheelie bins which are equipped with side trunnions.
- Operated via gearbox and a 6M endless chain for safe use from low levels.
- Constructed with zinc plated twist screws to ensure safe attachment to forklift trucks.
- Bright orange painted finish for clear visibility and safety.
- Safe working load: 600kg.
- Ratchet tensioner strap to leading edge.
- Max fork section: 150 x 60mm.
- Centre of Gravity: 1240-1410mm.



NEW
UK MADE

Code	Price € each
435919RN6	6177.00



C Load protection shock absorber

- Help to reduce damage to fragile loads when being loaded/unloaded by forklift trucks.
- Simply attach to the face of the fork and is magnetically held in place.
- Designed for best use where load in uneven as IDSA 3mm rubber fingers mould to the load to increase protection and reduce damage to goods.
- Temperature range -140 – 100 degrees Celsius.
- 30mm lost load centre.
- Choice of lengths.
- Two required per forklift.

NEW



Code	Length mm	Price € each
435897RN6	400	243.00
435898RN6	420	334.00
435899RN6	450	342.00
435900RN6	540	383.00

N.B. Price is for a single item.

D Load buffer

- Load buffer is designed to reduce damage to fragile loads from the fork back when being unloaded/loaded.
- Simply attach to the face of the fork and is magnetically held in place.
- 25mm thick encapsulated foam pads.
- Can be easily removed/placed between trucks on one site.
- Bright orange painted finish for clear visibility and safety.
- Choice of lengths suitable for a variety of fork sections.

NEW



Code	Length mm	Max. fork section mm	Price € each
435958RN6	460	80 x 50	617.00
435959RN6	460	100 x 50	705.00
435960RN6	560	100 x 50	739.00
435961RN6	560	130 x 60	806.00
435962RN6	720	150 x 60	849.99

N.B. Price is for a single item.