



H Portable I-bar sealer

- Single bar impulse heat sealer with integral film unroller and separator bar. • Economical option for lower volume applications.
- Suitable with layflat tubing or shrink wrap.
- Portable and requires no warm-up time.
- Requires standard 240V 13amp power supply.
- Power: 350W (402967RN6 is 700W)
- Sealing time: 1-3 seconds.
- Incorporates storage aerial for a hot air shrink gun (gun available separately).



Code	Seal width mm	L x W x H mm	Price € each
402967RN6	800	310 x 980 x 250	583.00

J Impulse heat sealer with cutter

- Aluminium body and seal bar for greater rigidity.
- Suitable to seal PE, PP, PA and PVC foil together with thinner double coated materials. • Adjustable sealing time.
- Sealing wire tensioning unit maintains constant seal width. • Seal width 2.5mm.
- Integral safety film cutter to trim excess film.
- No mechanical switches for optimum reliability.
- Power supply 230V 50Hz.
- Max. seal thickness: Polythene - 200mu bag, total 400mu / Polypropylene - 80mu bag, total 160mu / PVC - 30mu bag, total 60mu.



Code	Cutting width mm	Price € each
378100RN6	220	345.00
378101RN6	320	368.00
378104RN6	420	432.00
378111RN6	620	627.00

L Single bar heat sealer

- Seals up to 2 x 150 micron film. • Supplied with a spare parts kit.
- Choice with or without cutter. • Available in 4 widths.



Max sealing width mm	Without cutter Code	Price € each	With cutter Code	Price € each
200	378121RN6	90.09	378127RN6	185.00
300	378128RN6	127.00	378131RN6	158.00
400	378133RN6	181.00	378134RN6	203.00
500	378135RN6	188.00		

I Hot air gun

- Hot air gun makes this a complete system for low-volume shrink wrapping operations with the I-bar heat sealers.
- For PVC shrink wrap.
- 1200W.



Code	Price € each
426303RN6	126.00

K Film unroller

- Suitable for shrink wrap and polythene layflat tubing.
- Integral separator bar for folded shrink film.
- Available in two roll widths.
- Shrink wrap and layflat tubing available separately.



Code	Max. roll width mm	Price € each
415385RN6	450	101.00
415386RN6	600	90.09

M Portable hand held heat sealer

- Portable heat sealing for items too large for bench mounted sealers.
- Easy to use. • Power consumption 25-50W.
- Max. seal thickness: 2 x 200 micron. • Max. seal width: 150mm.
- Max. heat: 220°C.
- Temperature regulator.
- Weight 1.22kg.



Code	Description	Materials	Price € each
308494RN6	Flat sealer	Polythene bags and tube	129.00
308496RN6	Crimp sealer	Cellophane, polypropylene, foil and other laminates	158.00