

Wheels & Castors

Wheels

A Rubber tyred wheel with polypropylene centre

- 1" dia. bore.
- Plain or roller bearing.



Code	Wheel dia. mm	Tread width mm	Hub width mm	Load cap. kg	Bearing type	Price € each
330828RN6	200	76	76	250	Plain	51.64
330829RN6	200	76	63	250	Roller	53.30
330830RN6	280	80	66	250	Plain	65.29
330831RN6	280	80	75	250	Roller	66.89
330832RN6	330	70	66	250	Plain	70.39
330833RN6	330	70	75	250	Roller	77.34
330834RN6	355	75	66	300	Plain	89.84
330835RN6	355	75	63	300	Roller	94.04
330836RN6	400	90	66	350	Plain	112.00
330837RN6	400	90	63	350	Roller	114.00

B Rubber tyred wheel with pressed steel centre

- 1" dia. bore.
- Plain or roller bearing.



Code	Wheel dia. mm	Tread width mm	Hub width mm	Load cap. kg	Bearing type	Price € each
330648RN6	330	70	66	300	Plain	108.00
330650RN6	330	70	63	300	Roller	117.00
330649RN6	330	70	83	300	Ball	174.00
330651RN6	350	75	66	400	Plain	116.00
330653RN6	350	75	63	400	Roller	119.99
330652RN6	350	75	83	400	Ball	179.99
330654RN6	400	90	66	600	Plain	151.00
330656RN6	400	90	63	600	Roller	158.00
330655RN6	400	90	83	600	Ball	203.00

C Puncture proof wheel with patterned tread

- Closed cell microcellular polyurethane tyre.
- Polypropylene centre.
- More sizes online.



Code	Wheel dia. mm	Tread width mm	Bore dia. mm	Hub width mm	Load cap. kg	Bearing type	Price € each
427167RN6	260	75	25	75	200	Plain	83.10
427168RN6	260	75	25	75	200	Roller	87.34
376778RN6	260	85	20	75	120	Plain	51.09
376779RN6	260	85	25	75	120	Plain	48.59
427169RN6	285	88	20	75	150	Plain	108.00
427170RN6	285	88	20	75	150	Roller	112.00
427171RN6	285	88	25	75	150	Plain	107.00
427172RN6	285	88	25	75	150	Roller	112.00
427173RN6	390	90	20	65	200	Plain	168.00
427174RN6	390	90	20	65	200	Roller	173.00

D Puncture proof wheel with ribbed tread

- Closed cell microcellular polyurethane tyre.
- Polypropylene centre.



Code	Wheel dia. mm	Tread width mm	Bore dia. mm	Hub width mm	Load cap. kg	Bearing type	Price € each
427159RN6	200	52	20	60	50	Plain	48.34
427160RN6	200	52	20	60	50	Roller	52.60
427161RN6	200	52	25	60	50	Plain	48.34
427162RN6	200	52	25	60	50	Roller	52.60
427163RN6	370	80	20	65	218	Plain	119.99
427164RN6	370	80	20	65	218	Roller	124.00
427165RN6	370	80	25	65	218	Plain	119.99
427166RN6	370	80	25	65	218	Roller	124.00

E Puncture proof wheel with yellow tyre

- Microcellular rubber tyre.
- Polypropylene centre.
- Offers the same performance as pneumatic tyred wheels but without the risk of punctures.



Code	Wheel dia. mm	Tread width mm	Bore dia. mm	Hub width mm	Load cap. kg	Bearing type	Price € each
383739RN6	260	80	20	65	180	roller	93.64

F Nylon wheel

- Suitable for a vast variety of industrial uses.



Code	Wheel dia. mm	Tread width mm	Bearing type	Bore dia. mm	Hub width mm	Load cap. kg	Price € each
331531RN6	63	22	plain	9.5	33	122	7.04
331532RN6	75	25	plain	12	40	170	6.34
331533RN6	100	32	plain	15	48	270	8.34
331534RN6	100	32	roller	15	48	270	23.79
331537RN6	150	38	plain	20	60	520	31.34
331538RN6	150	38	roller	20	60	520	45.74