

Wheels & Castors Castors – Light & Medium Duty

A Polypropylene plate fixing castor

- Plain bearings.
- Fixing centres:
38x38mm - 48x48mm
M6 (Ø50/75mm
wheels), or 52x52mm
- 58x58mm M8
(Ø100/125mm wheels).



Swivel (A1)

Swivel with total-stop brake (A2)

Code	No.	Wheel dia. mm	Tread width mm	Top plate size mm	Fitted height mm	Load cap. kg	Price € each
384349RN6	A1	50	20	60 x 60	69.5	50	5.19
384350RN6		75	25	60 x 60	100	70	6.39
384351RN6		100	27	76 x 76	134	80	10.69
384352RN6	A2	125	27	76 x 76	155.5	100	12.39
384353RN6		50	20	60 x 60	69.5	50	6.79
384354RN6		75	25	60 x 60	100	70	8.79
384355RN6		100	27	76 x 76	134	80	14.44
384356RN6		125	27	76 x 76	155.5	100	18.09

B Polypropylene bolt hole fixing castor

- Plain bearings.
- Fixing hole: M10 (Ø50/75mm wheel), M12 (Ø100/125mm wheel).



Swivel (B1)

Swivel with total-stop brake (B2)

Code	No.	Wheel dia. mm	Tread width mm	Fitted height mm	Load cap. kg	Price € each
384357RN6	B1	50	20	68	50	3.94
384358RN6		75	25	98	70	6.74
384359RN6		100	27	131.5	80	10.99
384360RN6	B2	125	27	153	100	12.64
384361RN6		50	20	68	50	6.44
384362RN6		75	25	98	70	9.09
384363RN6		100	27	131.5	80	13.99
384364RN6		125	27	153	100	15.64

C Polypropylene plate fixing twin wheel castor

- Plain bearings.
- Top plate size 60 x 60mm.
- Fixing centres 38x38mm to 48x48mm, M6.



Swivel (C1)

Swivel with total-stop brake (C2)

Code	No.	Wheel dia. mm	Tread width mm	Fitted height mm	Load cap. kg	Price € each
384991RN6	C1	50	20 x 2	71	80	9.94
384992RN6		75	25 x 2	103	100	14.64
384993RN6	C2	50	20 x 2	71	80	12.44
384994RN6		75	25 x 2	103	100	20.89

D Polypropylene bolt hole fixing twin wheel castor

- Plain bearings.
- M10 fixing hole.



Swivel (D1)

Swivel with total-stop brake (D2)

Code	No.	Wheel dia. mm	Tread width mm	Fitted height mm	Load cap. kg	Price € each
384995RN6	D1	50	20 x 2	71	80	7.74
384996RN6		75	25 x 2	100	100	13.89
384997RN6	D2	50	20 x 2	71	80	11.84
384998RN6		75	25 x 2	100	100	20.09

E TPR tyred, nylon centre plate fixing castor

- Thermoplastic rubber (TPR) tread.
- Plain bearings.
- Fixing centres:
38x38mm to 48x48mm
M6 (Ø50/75mm
wheels), or 52x52mm
to 58x58mm M8
(Ø100/125mm wheels).



Swivel (E1)

Swivel with total-stop brake (E2)

Code	No.	Wheel dia. mm	Tread width mm	Top plate size mm	Fitted height mm	Load cap. kg	Price € each
384365RN6	E1	50	20	60 x 60	69.5	50	3.94
384366RN6		75	25	60 x 60	100	70	6.70
384367RN6		100	27	76 x 76	134	80	11.14
384368RN6	E2	125	27	76 x 76	157	100	12.94
384369RN6		50	20	60 x 60	69.5	50	6.79
384370RN6		75	25	60 x 60	100	70	9.09
384371RN6		100	27	76 x 76	134	80	14.19
384372RN6		125	27	76 x 76	157	100	16.00

F TPR tyred, nylon centre bolt hole fixing castor

- Thermoplastic rubber (TPR) tread.
- Plain bearings.
- Hole fixing: M10 (Ø50/75mm wheel), M12 (Ø100/125mm wheel).



Swivel (F1)

Swivel with total-stop brake (F2)

Code	No.	Wheel dia. mm	Tread width mm	Fitted height mm	Load cap. kg	Price € each
384373RN6	F1	50	20	68	50	4.34
384374RN6		75	25	98	70	7.04
384375RN6		100	27	131.5	80	11.44
384376RN6	F2	125	27	154.5	100	13.20
384377RN6		50	20	68	50	6.64
384378RN6		75	25	98	70	9.44
384379RN6		100	27	131.5	80	14.59
384380RN6		125	27	154.5	100	16.34