

D Bottom emptying forklift skips

- Sturdy steel construction with smooth interior sides.
- Cable operated door release - can be used from the driver's seat.
- Rubber cushioning to lessen the impact when trap door is opened.
- Can be secured to prevent slipping and unintentional emptying.
- 100mm ground clearance - suitable for use with pallet trucks.
- Stackable, and fitted with 40mm dia. crane holes at each corner.
- Optional galvanised lid and guide plates shown, available on request.
- CE marked.



Up to
2000L



Skip with optional
galvanised lid

Skip shown with optional
galvanised guide plates

Code	Vol. m³	L x W x H mm	Capacity kg	Wt. kg	Price € each
386337RN6	0.50	800 x 1200 x 860	1000	125	2024.00
386338RN6	0.75	800 x 1200 x 1160	1000	144	2132.00
386339RN6	1.00	1000 x 1200 x 1160	1250	158	2257.00
386340RN6	1.50	1000 x 1800 x 1160	1500	202	2749.00
386341RN6	2.00	1000 x 1800 x 1460	1500	232	2918.00



Fork sleeve inside dimensions in mm

Volume m³	A	B	C
0.50 - 1.00	415	185	75
1.50 - 2.00	615	185	75

E Mobile bottom emptying forklift skips

- For simple, effective disposal of light to medium weight waste.
- Automatic remote emptying via the base release mechanism, without the driver leaving the safety of his seat.
- 125mm dia. nylon castors fitted as standard.
- Internally reinforced sides and lap welded corners.
- Unique automatic releasing and locking mechanism.
- Maximum fork section 150 x 50mm at 683mm centres.
- Zinc plated heel pins for safe attachment.
- Highly visible bright orange paint finish.
- UKCA & CE marked.



Up to
950KG

Up to
1450L

Code	Volume m³	L x W x H mm	Capacity kg	Weight kg	Price € each
407565RN6	0.80	850 x 1050 x 1170	550	140	2195.00
407566RN6	1.20	750 x 1200 x 1170	750	175	2637.00
407567RN6	1.45	1050 x 1500 x 1170	950	190	3018.00

F Wheelie bin tipping stations

- Manual (hand or foot pump) or electric (12Vdc or 230Vac) powered lift.
- Load capacity 110kg.
- Suitable for 120 and 240 ltr. wheelie bins.
- 135° max. tipping angle.
- Max. emptying height 1480mm.
- Blue painted steel frame.
- Overall (lowered) L x H: 1570 x 1720mm.
- On 2 fixed and 2 swivel 180mm dia. braked rubber castors.
- Width: 980mm (manual), 880mm (electric).
- N.B. 418476RN6 is supplied without a 12V battery charger - available as an optional extra.



12Vdc battery powered



Manual hand pump



230Vac powered

Code	Description	Price € each
418474RN6	Manual, foot pump	4394.00
418475RN6	Manual, hand pump	4394.00
418476RN6	Powered, 12Vdc	6451.00
418477RN6	Powered, 230Vac	6463.00
418478RN6	12V Battery charger	349.99



Manual hand pump

110
KG